

Electrical Heaters

NEW!



GEMAS Heatrone PRO

Electrical Heater with plastic body made of fiberglass reinforced PP. Triphase. Complete with magnetic contactors, thermal switch and flow switch. Control board has seven segment digital thermostat and led indicator for operation, as well as power control. Heating elements made of AISI 316 Stainless Steel. Timer is optional. Please add "O" at the end of existing code when ordering.

Description	Code	Pieces/box	Weight Kg	Volume m ³
• 6 kW Electrical Heater	10120	1		
• 9 kW Electrical Heater	10121	1		
• 12 kW Electrical Heater	10122	1		
• 15 kW Electrical Heater	10123	1		
• 18 kW Electrical Heater	10124	1		

NEW!



GEMAS Heatrone PRO - Ti

Ditto, but heating elements made of Titanium.

Description	Code	Pieces/box	Weight Kg	Volume m ³
• 6 kW Electrical Heater	10120T	1		
• 9 kW Electrical Heater	10121T	1		
• 12 kW Electrical Heater	10122T	1		
• 15 kW Electrical Heater	10123T	1		
• 18 kW Electrical Heater	10124I	1		

NEW!



GEMAS Heatrone

Electrical Heater with plastic body made of fiberglass reinforced PP. Triphase. Complete with flow switch and mechanical thermostat. Heating elements made of AISI 316 Stainless Steel.

Description	Code	Pieces/box	Weight Kg	Volume m ³
• 6 kW Electrical Heater	10130	1		
• 9 kW Electrical Heater	10131	1		
• 12 kW Electrical Heater	10132	1		
• 15 kW Electrical Heater	10133	1		
• 18 kW Electrical Heater	10134	1		

NEW!



GEMAS Heatrone - Ti

Ditto, but heating elements made of Titanium.

Description	Code	Pieces/box	Weight Kg	Volume m ³
• 6 kW Electrical Heater	10130T	1		
• 9 kW Electrical Heater	10131T	1		
• 12 kW Electrical Heater	10132T	1		
• 15 kW Electrical Heater	10133T	1		
• 18 kW Electrical Heater	10134T	1		

Electrical Equipments For Pools



GEMAS HEATRONE PRO MINI ELECTRICAL HEATER



"Heatron electric heater is a device designed and manufactured only for use in swimming pools and SPAs.

PRODUCT FEATURES

- 1kW, 2kW, 3kW, 4kW and 6kW heating capacity
- Single-phase - Three-phase electrical connection
- Heating resistances Titanium or AISI 316 stainless steel
- Complete with digital or mechanical thermostat and flow switch,
- Heat-resistant plastic body
- Minimum flow 6 m³/h,
- Max. working pressure: 2 bar
- Ø 50 mm PVC union pipe connection

Minimum Flow	90 l/min
Maksimum Flow	300 l/min
Power	230V 1 – Phase 1 – 3 kW
	230V 3 – Phase 3 – 6 kW
	400V 3 – Phase 3 – 6 kW
Maksimum Pressure	2 bar
Maksimum Temperature	45°C

